



Product Data Sheet

Anti-Spall 50/50

234 Harvestore Dr · DeKalb, IL 60115
Phone: 815-754-5700 · Fax: 815-754-5702
www.rightpointe.com

DESCRIPTION: Anti-Spall 50/50 is a solution of mineral spirits and boiled linseed oil that functions as a fast drying, penetrating concrete sealer. It is designed to prevent the spalling and scaling of concrete, especially those structures that are exposed to the destructive effects of de-icing salts, freeze-thaw cycles, and ponding surface water. Anti-Spall 50/50 penetrates the surface of concrete to seal and protect, extending the concrete service life.

- Will cause an amber coloration on applied surfaces
- Meets the United States EPA regulations with a maximum 400 g/L VOC content
- Penetrates into concrete surface prolonging the service life
- Prevents scaling and spalling
- Can also be used on wood structures to preserve and seal
- Ready to use

SPECIFICATIONS: Anti-Spall 50/50 meets all requirements of ASTM D260, ASTM D235, AASHTO M233, and IL DOT section 1023.01.

PACKAGING:

- 55 gallon drums
 - Item #: 3910-001

USE AND APPLICATIONS: The appropriate time of application for the maximum penetration of the sealer is after the final cure phase; most effectively after 28 days of curing. Before application of Anti-Spall 50/50, clean surface debris from the concrete to be treated. Once surface is clean and dry, spray one coating of Anti-Spall 50/50 over the surface of the concrete; avoid pooling on the concrete surface. Anti-Spall 50/50 may be applied with a standard hand-held sprayer or power sprayer; a short-napped roller is recommended for brush application. A second application of Anti-Spall 50/50 can be applied immediately after the first. Two coats are recommended for maximum seal. Restrict foot traffic until surface is completely dry.

- Bridge decks
- Sidewalks
- Barrier medians
- Driveways
- Parking garages

FEATURES AND BENEFITS:

- Coverage rate – first coat approximately 200 sq ft/gal, second coat approximately 600 sq ft/gal
- Drying time – approximately 3 hours (weather dependent)

RESTRICTIONS:

- Water based, incompatible with solvent containing products
- Ready to use - DO NOT DILUTE
- For optimum results, light mixing is recommended (excessive agitation will cause foaming)
- Use a spray rate of approximately ½ gallon per minute, not exceeding 45 PSI of pressure
- Do not allow to freeze
- Use only when ambient temperature exceeds 40 °F for 24 hours
- May darken concrete surfaces that have been densely troweled

TECHNICAL SERVICE: For conditions not specified, application procedures not noted, contact Right / Pointe, LLC (815) 754-5700.

LIMITED WARRANTY: Every reasonable effort is made to apply RIGHT / POINTE, LLC exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RIGHT / POINTE, LLC MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and RIGHT / POINTE, LLC shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the RIGHT / POINTE, LLC Technical Manager.

October 16, 2017