



RIGHT PRIME

SOLVENT-BASED ADHESIVE

DESCRIPTION

RIGHT PRIME is a solvent based primer recommended for use with RIGHT ROLL SELF-ADHERING WATERPROOFING MEMBRANE & PAVE PATCH-GRAY HOT APPLIED MASTIC.

USE AND APPLICATIONS

RIGHT PRIME does not require additional mixing or diluting before use. It can be applied on vertical or horizontal surfaces by rolling or brushing the surface after the area has been prepped for installation of our RIGHT ROLL & PAVE PATCH-GRAY. Suitable preparation includes clearing the area of unstable pavement, rocks and dust, and then drying completely. After applying, allow RIGHT PRIME to dry for one hour or until the entire surface maintains a tacky feeling. Concrete surfaces should be cured at least 72 hours before applying RIGHT PRIME. Along with being used as an adhesive, RIGHT PRIME can also dustproof any clean and smooth surface free of contaminants.

- Ready to use
- For vertical and horizontal applications
- High solids, high performance

PACKAGING

- 5 Gallon Pail
- 55 Gallon Drum

COVERAGE

250 to 300 sq ft / gal

SHELF LIFE

Three years when stored indoors in unopened containers at temperatures between 40° to 90° F (4° to 32° C)

PRECAUTIONS

Do not dilute; use as is. Avoid over application, when material pools it takes longer to dry. Use with adequate ventilation and care. Material has a flash point of 50° F.

CLEAN UP

Right Prime may be removed from surfaces using mineral spirits.

TECHNICAL SERVICE

For conditions not specified, application procedures not noted, contact: Right Pointe Company (888) 755-5700.

LIMITED WARRANTY

Every reasonable effort is made to apply RIGHT POINTE COMPANY exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RIGHT POINTE COMPANY MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and RIGHT POINTE COMPANY shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the RIGHT POINTE COMPANY Technical Manager.

Right / Pointe Company • 234 Harvestore Dr., Dekalb, IL 60115

toll free: 888.755.5700 • office: 815.754.5700 • fax: 815.754.5702 • www.rightpointe.com

PRODUCT DATA SHEET



MANUFACTURER : RIGHT POINTE COMPANY
 ADDRESS : 234 Harvestore Drive
 : P.O. BOX 467
 : DeKalb, IL 60115

- HMIS -

TELEPHONE : 888-755-5700
 FAX : 815-754-5702

Health	2
Flammability	3
Reactivity	0
Personal Protection	

(Hazard Rating: 0=Least, 1=Slight, 2=Moderate, 3=High, 4=Extreme, *=Chronic)

TRADE NAME : RIGHT PRIME

APPEARANCE : Black, Coarse Liquid; Solvent Odor.

No.	Component	CAS#	% by Weight	SARA	VAPOR PRESSURE (mm Hg @ 20° C)	LEL (@ 25° C)
1.	Toluene 1	08-88-3	45-50	Yes	26 mm Hg @ 25° C	1.1
2.	Petroleum Oil	64742-65-0	5-10	No	N/A	N/A

BOILING POINT : 300 – 320° F

EVAPORATION RATE : Not Applicable

VAPOR DENSITY : >1

FLASH POINT : Product will not flash.

FLAMMABILITY CLASSIFICATION : Yes, under Class B, Division 3.

EXTINGUISHING MEDIA : DO NOT USE WATER! Foam, dry chemical, CO2

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS : Do not direct water on substance. Treat as a fuel oil fire. Water may be used to cool closed containers. In a substance fire, use self-contained breathing apparatus.

UNUSUAL FIRE/EXPLOSION HAZARDS : None Recognized.

STABILITY : Stable.

HAZARDOUS POLYMERIZATION : Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS : Combustion may yield sodium oxides and silicon oxides. Do not breathe fumes. Wear appropriate protective equipment.

CONDITIONS AND MATERIALS TO AVOID : Strong oxidizing agents.

EYE CONTACT: This product may cause irritation, blurred vision. Move victim to an area with fresh air and flush the eyes for at least 15 minutes with water. If irritation continues, seek medical help.

SKIN CONTACT: Remove any contaminated clothing and wash exposed skin with soap and water. If redness or swelling persists, seek medical attention.

INHALATION: This product may cause headaches and/or dizziness. This material is for exterior use only.

INGESTION: This product has a low order of toxicity. Do not induce vomiting. Consult a physician immediately.

AGGRAVATED MEDICAL CONDITIONS: Persons with a history of chronic skin or respiratory disorders may be at increased risk for a worsening of their condition from exposure to this product.

RESPIRATORY PROTECTION: Normally not needed. If TLV is exceeded, use approved NIOSH/MSHA respirator.

PROTECTIVE CLOTHING: Cover eyes with safety glasses/goggles or splash shield. Do not wear contact lenses. Handlers should also wear long sleeves, pants that cover entire legs, and thick rubber or neoprene gloves to minimize skin exposure.

ADDITIONAL PROTECTIVE MEASURES: Chemical splash proof goggles recommended. If material is sprayed goggles are a must.

SPILL OR LEAK PROCEDURES:

LARGE SPILLS: Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above.

SMALL SPILLS: Place in non-leaking containers; seal tightly for proper disposal.

DISPOSAL: Observe all federal, state and local regulations regarding proper disposal.