



## RIGHT RELEASE OIL - CITRUS

### **DESCRIPTION**

RIGHT RELEASE OIL - CITRUS is a film forming treatment that prevents the bonding of fresh concrete mix to forms, tools, and equipment, without leaving behind an offensive odor. Composed of non-staining natural oils, RIGHT RELEASE OIL - CITRUS reacts with excess lime on the surface of the concrete to give a quick, clean stripping from any form work.

- Provides economical smooth concrete surfaces
- Lengthens form life
- Natural citrus scent

### **SPECIFICATIONS**

This product meets the maximum VOC content limit (450 g/L) for form release compounds as required by the U.S. EPA Architectural Coatings Rule and the rigid specifications set forth by the Ozone Transport Commission (OTC).

### **USE AND APPLICATIONS**

For use on various types of forms (wood, steel, fiberglass, aluminum). Treat and season forms prior to each use with brush, roller or hand sprayer (maximum setting at 25-30 PSI with fan type tip). Avoid excess run-off or ponding by only applying a thin coat of RIGHT RELEASE OIL - CITRUS.

- FOR EXTERIOR USE ONLY
- NOT TO BE USED AS A TILT-UP BONDBREAKER

### **FEATURES AND BENEFITS**

- Minimizes stripping time
- Provides a clean cast on pre-cast products
- Inhibits concrete buildup on equipment
- Can be painted over

### **PACKAGING**

- 5 Gallon Pail
- 55 Gallon Drum
- 275 Gallon Tote

### **COVERAGE RATES**

Plywood/Lumber.....600-1000 sq ft/gal  
Aluminum/Steel.....1000-2000 sq ft/gal

DO NOT OVER APPLY --- NOT FOR USE ON STYROFOAM

### **CLEAN UP PROCEDURE**

Soap and water will clean application equipment.

### **WARNINGS**

ADEQUATE VENTILATION NECESSARY DURING APPLICATION.

FUMES MAY IRRITATE SKIN AND EYES.

Refer to the Safety Data Sheet for additional health and safety information.

### **TECHNICAL SERVICE**

For conditions not specified, application procedures not noted, contact: Right Pointe Company (888) 755-5700.

### **LIMITED WARRANTY**

Every reasonable effort is made to apply RIGHT POINTE COMPANY exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, RIGHT POINTE COMPANY MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and RIGHT POINTE COMPANY shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the RIGHT POINTE COMPANY Technical Manager.

Right / Pointe Company • 234 Harvestore Dr. Dekalb, IL 60115

toll free: 888.755.5700 • office: 815.754.5700 • fax: 815.754.5702 • www.rightpointe.com



MANUFACTURER : RIGHT POINTE COMPANY  
 ADDRESS : 234 Harvestore Drive  
 : P.O. BOX 467  
 : DeKalb, IL 60115

- HMIS -

Health	1
Flammability	1
Reactivity	0
Personal Protection	

TELEPHONE : 888-755-5700  
 FAX : 815-754-5702

MFG. CODE I.D. : CHLQ-003 (Hazard Rating: 0=Least, 1=Slight, 2=Moderate, 3=High, 4=Extreme, \*=Chronic)

TRADE NAME : RIGHT RELEASE - CITRUS

FLASH POINT : 195° F

FLAMMABILITY CLASSIFICATION : NFPA : Combustible Liquid – Class IIIA  
 : DOT : Not regulated

EXTINGUISHING MEDIA : Water, foam, dry chemical, or CO2.

SPECIAL FIRE FIGHTING PROCEDURE : None recognized.

UNUSUAL FIRE/EXPLOSION HAZARDS : None recognized.

STABILITY : Stable.

HAZARDOUS POLYMERIZATION : Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS : Carbon dioxide, monoxide. Do not breathe fumes. Wear protective equipment.

EYE CONTACT: Move victim to an area with fresh air and flush the eyes for at least 15 minutes with water. If irritation continues, seek medical help.

SKIN CONTACT: Remove any contaminated clothing and wash exposed skin with soap and water. If redness or swelling persists, seek medical attention.

INHALATION: Handlers should use this product in well-ventilated areas only to prevent exposure to higher vapor concentrations. If exposure exceeds the PEL/TLV, use the appropriate NIOSH approved respirator. If inhaled, move victim to an area with fresh air and away from the material. If breathing problems develop and/or irritation continues, have a qualified person administer oxygen and contact a physician immediately. If the victim is not breathing, perform CPR and seek immediate medical attention.

INGESTION: Do NOT induce vomiting. If victim does start to vomit, keep his/her head below the hips to prevent aspiration into the lungs. If victim is conscious, dilute by giving water or milk. Contact a physician or poison control facility and transport the victim to emergency facilities immediately.

CLOTHING: Cover eyes with safety glasses/goggles or splash shield. Do not wear contact lenses. Handlers should also wear long sleeves, pants that cover entire legs, and gloves to minimize skin exposure.

**SPILL OR LEAK PROCEDURES:**

LARGE SPILLS: Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut-off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above.

SMALL SPILLS: Place in non-leaking containers; seal tightly for proper disposal.

DISPOSAL: Observe all federal, state and local regulations regarding proper disposal.